



PHRD SG

Pictured: Various PHRD-SG combination seal solutions

Standard Mechanical Seals with segmented ring technology

FEATURES AND TECHNICAL DATA:

- **Segmented ring technology—individual adjustment to cable diameters on site**
- **Split seal for retrofit installation**
- **Gastight and watertight**
- **Solid 0.197 inch (5 mm) stainless steel press plate**
- **EPDM rubber**



CORE DRILL HOLE / WALL SLEEVE ID RANGE inch (mm)	NUMBER OF CABLES	CABLE DIAMETER OD RANGE inch (mm)	CATALOG NUMBER	PRODUCT EXAMPLE
3.937 – 4.016 (100 mm)	8	0.157 – 0.650 (4 – 16,5 mm)	PHRD4-SG-8	
	5	0.315 – 1.181 (8 – 30 mm)	PHRD4-SG-5	
	of which 2			
4.921 – 5.000 (125 mm)	of which 3	0.157 – 0.650 (4 – 16,5 mm)		
	3	0.394 – 1.575 (10 – 40 mm)	PHRD5-SG-3	
	6	0.236 – 1.220 (6 – 31 mm)	PHRD5-SG-6	
5.906 – 5.985 (150 mm)	10	0.157 – 0.650 (4 – 16,5 mm)	PHRD5-SG-10	
	9	0.236 – 0.984 (6 – 25 mm)	PHRD6-SG-9	
	10	0.315 – 1.181 (8 – 30 mm)	PHRD6-SG-10	
	of which 4			
7.874 – 7.953 (200 mm)	of which 6	0.157 – 0.650 (4 – 16,5 mm)		
	7	0.236 – 2.126 (6 – 54 mm)	PHRD8-SG-7	
	of which 3			
	of which 4	0.236 – 1.024 (6 – 26 mm)		
	15	0.394 – 1.260 (10 – 32 mm)	PHRD8-SG-15	
	of which 7			
of which 8	0.138 – 0.650 (3,5 – 16,5 mm)			

If either your OD or ID falls outside the ranges listed, please contact us for additional solutions.

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

CONTACT US

1-800-328-9384 Toll Free
1-651-430-2270 Main
1-651-430-3634 Fax

email:
support@polywater.com

American Polywater Corp.
11222 60th Street N
Stillwater, MN 55082 USA



polywater-haufftechnik.com