

PHSI-150-DG





Pictured: Various installation stages for PHSI-150-DG-3

Cable Entries for the HSI 150 system and retrofit sealing

FEATURES AND TECHNICAL DATA:

- Split seal for retrofit installation
- Individual adjustment to the diameter of the installed cable diameters on site
- Labeled segment rings for easy installation
- Constructed of glass fiber reinforced polyamide
- Screws and nuts made of stainless steel V4A (AISI 316L)
- Pressure-tight up to 36.30 PSI (2.5 bar)

		
HSI 150-DG Segment layers are labeled with cable OD's	Pressure plate cover PHSI-150-PA-3	Medium voltage cables sealed with PHSI-150-DG-6

PACKAGE DESCRIPTION	CABLE DIAMETER OD RANGE INCH (mm)	NUMBER OF CABLES/PIPES	CATALOG NUMBER	PRODUCT EXAMPLE
Split system cover with 1 opening including split adapter ring	1.417 – 2.756 (36 – 70 mm)	1	PHSI-150-DG-1	
Split system cover with 1 opening including split adapter ring	2.756 – 4.409 (70 – 112 mm)	1	PHSI-150-DG-1L	
Split system cover with 3 openings including split adapter ring and 3x blind plugs	0.945 – 2.126 (24 – 54 mm)	3	PHSI-150-DG-3	
Split system cover with 6 openings including split adapter ring and 6x blind plugs	0.394 – 1.417 (10- 36 mm)	6	PHSI-150-DG-6	

Included per system cover PHSI-150-DG: lubricant stick, cutter knife, cleaning cloth.
Blind plugs are included with PHSI-150-DG-3 and the PHSI-150-DG-6 to seal openings that might not be used.



Matching accessories such as pressure plate covers and installation toolkit are located on the accessories flyer



IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

CONTACT US

1-800-328-9384 Toll Free
1-651-430-2270 Main
1-651-430-3634 Fax

email:
support@polywater.com

American Polywater Corp.
11222 60th Street N
Stillwater, MN 55082 USA

