



# PGKD

MODULAR SEAL WITH PATENTED VISUAL INSTALLATION INDICATOR



## FEATURES AND BENEFITS

## The Only Modular Seal on the Market that Visually Indicates Proper Installation

The PGKD patented installation control visually indicates when the seal is secure. Crews, engineers, and owners get the added peace of mind and security that the PGKD was installed properly. Gas, water, sewer, and electrical crews will appreciate having the nuts molded into the pressure plate, a design that greatly reduces the risk of lost parts. Available in EPDM or NBR rubber.

- **VISUAL INSTALLATION INDICATOR**  
Integrated, visual installation control – no torque wrench required
- **NO RETIGHTENING REQUIRED**  
Seal remains secure after installation
- **GASTIGHT AND WATERTIGHT**  
Up to 72 psi (5 bar)
- **NO LOOSE PARTS**  
Nuts molded into the pressure plates
- **DURABLE**  
All metal parts made of high-quality stainless steel V4A (AISI 316L)



# Polywater | Hauff-Technik—PGKD Modular Seal



The visual indication provides confidence that the seal is secure.

MODULAR SEAL PGKD, EPDM (ALSO AVAILABLE IN NBR)						
ANNULAR SPACE INCH (MM)		CARRIER PIPE OD INCH (MM)		INSTALLATION DEPTH INCH (MM)	CATALOG #	
From	To	From	To			
0.5 inch (12.7mm)	0.629 (16mm)	0.838 (21.3 mm)	12.75 (323.9 mm)	2.95 (75 mm)	<b>PGKD-200-EPDMXX</b>	
0.629 (16.0 mm)	0.787 (20.0 mm)	0.98 (25.0 mm)	3.54 (90.0 mm)	2.95 (75 mm)	<b>PGKD-275-EPDMXX</b>	
0.728 (18.5 mm)	0.906 (23 mm)	2.894 (73.5 mm)	9.843 (250 mm)	3.937 (100 mm)	<b>PGKD-300-EPDMXX</b>	
0.915 (23.25 mm)	1.024 (26 mm)	2.374 (60.3 mm)	12.402 (315 mm)	3.937 (100 mm)	<b>PGKD-315-EPDMXX</b>	
0.945 (24 mm)	1.181 (30 mm)	7.000 (177.8 mm)	27.992 (711 mm)	4.331 (110 mm)	<b>PGKD-325-EPDMXX</b>	
1.0 (25.5 mm)	1.33 (34.0 mm)	1.18 (30.0 mm)	12.75 (323.9 mm)	4.72 (120 mm)	<b>PGKD-340-EPDMXX</b>	
1.25 (32.0 mm)	1.653 (42.0 mm)	1.57 (40.0 mm)	16.0 (406.4 mm)	4.72 (120 mm)	<b>PGKD-360-EPDMXX</b>	
1.437 (36.5 mm)	11.693 (43 mm)	8.031 (204 mm)	48.031 (1220 mm)	5.906 (150 mm)	<b>PGKD-400-EPDMXX</b>	
1.456 (37.0 mm)	1.90 (48.5 mm)	2.37 (60.3 mm)	12.75 (323.9 mm)	5.51 (140 mm)	<b>PGKD-410-EPDMXX</b>	
1.142 (29 mm)	1.378 (36 mm)	8.031 (204 mm)	48.031 (1220 mm)	4.921 (125 mm)	<b>PGKD-425-EPDMXX</b>	
1.772 (45 mm)	2.047 (52 mm)	8.031 (204 mm)	48.031 (1220 mm)	5.906 (150 mm)	<b>PGKD-440-EPDMXX</b>	
1.626 (41.3 mm)	1.909 (48.5 mm)	4.500 (114.3 mm)	48.031 (1220 mm)	5.906 (150 mm)	<b>PGKD-475-EPDMXX</b>	
2.441 (62 mm)	2.815 (71.5 mm)	7.626 (193.7 mm)	48.031 (1220 mm)	6.496 (165 mm)	<b>PGKD-500-EPDMXX</b>	
2.283 (58 mm)	2.500 (63.5 mm)	7.626 (193.7 mm)	48.031 (1220 mm)	6.496 (165 mm)	<b>PGKD-525-EPDMXX</b>	
1.969 (50 mm)	2.283 (58 mm)	8.031 (204 mm)	48.031 (1220 mm)	6.496 (165 mm)	<b>PGKD-575-EPDMXX</b>	
3.543 (90 mm)	3.858 (100 mm)	12.752 (323.9 mm)	118.110 (3000 mm)	8.071 (205 mm)	<b>PGKD-615-EPDMXX</b>	
3.031(77 mm)	3.307 (84 mm)	9.626 (244.5 mm)	78.740 (2000 mm)	6.496 (165 mm)	<b>PGKD-650-EPDMXX</b>	

X = NUMBER OF LINKS

\*The complete catalog number is derived from the number of links needed to seal the annular space.

Learn more about this product and other sealant solutions from Polywater | Hauff-Technik at [polywater-haufftechnik.com](http://polywater-haufftechnik.com)

[polywater-haufftechnik.com](http://polywater-haufftechnik.com) | [polywater.com](http://polywater.com)

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2021 American Polywater Corporation (08/21) LIT-PGKDFLYER/REV000

**Polywater**<sup>®</sup>  
Solutions at work.

American Polywater Corporation  
11222 60th Street N.  
Stillwater, MN 55082 USA

+1 651-430-2270  
+1 800-328-9384 Toll Free  
+1 651-430-3634 Fax  
email: [support@polywater.com](mailto:support@polywater.com)