



MECHANICAL SEALS WITH SUPER SEGMENTED RING TECHNOLOGY



The Only Lightweight One-Piece Seal with Super Segmented Ring Openings


The only one-piece mechanical seal with super segmented ring technology that adjusts to fit various electrical or telecommunication cables in the field. Seals core-drilled holes, sleeves, PVC, and rigid-steel conduits. Integrates with the PHSI options. Select the model that meets the sealing needs for your project and keep it in inventory.



FEATURES AND BENEFITS

- **ADJUSTABLE**
Individual adjustment to the installed cable diameters on site
- **MAINTAIN ACCURACY**
Segments with exact diameter marking
- **ADAPTABLE**
Split seal for retrofit installation
- **DURABLE DESIGN**
Pressure plates made of glass fiber reinforced polyamide
- **SMART DESIGN**
Form-fitting connections of the press plates

Polywater | Hauff-Technik—PHRK SSG Mechanical Seals



Segments with exact diameter marking.

CORE-DRILL HOLE/ WALL SLEEVE ID RANGE inch (mm)	NUMBER OF CABLES	CABLE DIAMETER OD RANGE inch (mm)	CATALOG #
3.937 – 4.016 (100 mm)	1	0.709 – 2.559 (18 – 65 mm)	PHRK4-SSG-1
	4	0.315 – 1.181 (8 – 30 mm)	PHRK4-SSG-4
5.906 – 5.985 (150 mm)	1	1.417 – 2.756 (36 – 70 mm)	PHRK6-SSG-1*
	1	2.756 – 4.409 (70 – 112 mm)	PHRK6-SSG-1L*
	3	0.945 – 2.126 (24 – 54 mm)	PHRK6-SSG-3
	6	0.394 – 1.417 (10 – 36 mm)	PHRK6-SSG-6
7.874 – 7.953 (200 mm)	1	4.331 – 6.378 (110 – 162 mm)	PHRK8-SSG-1*
	3	1.575 – 2.835 (40 – 72 mm)	PHRK8-SSG-3

*Without blind plugs

PRODUCT EXAMPLES



PHRK4-SSG-1



PHRK8-SSG-3



PHRK4-SSG-4



PHRK6-SSG-6

If OD or ID requirements fall outside the ranges listed, please contact us for additional solutions. polywater-haufftechnik.com

polywater-haufftechnik.com | polywater.com

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2021 American Polywater Corporation (08/21) LIT-PHRKFLYER/REV000

Polywater
Solutions at work.

American Polywater Corporation
11222 60th Street N.
Stillwater, MN 55082 USA

+1 651-430-2270
+1 800-328-9384 Toll Free
+1 651-430-3634 Fax
email: support@polywater.com