Polywater

hauff • technik

Solutions for the Gas Industry



PGKD

Modular Seal with visual installation indicator





FEATURES AND TECHNICAL DATA

- VISUAL INSTALLATION INDICATOR
 Integrated, visual installation control
 no tongue wrench required
- NO RE-TIGHTENING REQUIRED
 Seal remains secure after installation
- GASTIGHT AND WATERTIGHT Up to 72 psi (5 bar)
- NO LOOSE PARTS
 Nuts molded into the pressure plates
- All metal parts made of high-quality stainless steel V4A (AISI 316L)

PHPS

FEATURES AND TECHNICAL DATA

- SINGLE SOLUTION
 Ideal for smaller pipes and a range of pipe ODs
- **RELIABLE**Completely gastight and watertight
- REDUCES LABOR
 Cuts installation time down
- OPTIONS
 Designed for PVC, GRC, and Cast Iron pipe OD's



Polywater

hauff • technik



WALL SLEEVE and STANDARD MECHANICAL SEAL SYSTEM

PZVR

Wall Sleeve with proprietary coating



EFW-1

Alcohol Cleaning Wipe

FEATURES AND BENEFITS

- **EXCEEDS INDUSTRY STANDARDS** 99.8% pure anhydrous isopropyl alcohol
- GOOD SOLVENCY
 Removes mud, dirt, directional drilling fluid, and other contaminants
- LARGE CLEANING WIPE
 Use fewer wipes by cleaning more area per wipe
- SINGLE-USE WIPE
 Presaturated, field friendly cleaning wipe elminates contamination from use of bulk alcohol



FEATURES AND TECHNICAL DATA

- WATERTIGHT
 - Bonds to poured concrete with proprietary cement coating no puddle flange or engineered ridges needed
- REDUCES LABOR
 Designed with lightweight UPVC
- CUSTOMIZABLE LENGTH
 When ordered or cut on-site
- CLEAN AND DEBRIS-FREE Interior is protected with two PE end-caps
- DURABLE
 Will not rust or corrode

Polywater WLD

Leak Detector Fluid

FEATURES AND BENEFITS

- SUPERIOR PERFORMANCE Excellent wetting to plastics and metals
- MAXIMUM COVERAGE
 Fully coats and stays wetted to vertical surfaces, including PE, PVC and steel pipes
- SAFE
 Does not contain glycol ether
- SPECIALLY FORMULATE
 Dries clean without staining
- ACCURATE DELIVERY SYSTEM
 Convenient flip-top package allows for easy application and storage



polywater.com | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation (04/22) LIT-GASSOLUTIONSFLYER/REV000



American Polywater Corporation 11222 60th Street N. Stillwater, MN 55082 USA

- +1 800-328-9384 Toll Free
- +1 651-430-3634 Fax

email: support@polywater.com